UltraMax[™] ©lear Hose Data Sheet



Application:

An economic, lightweight, general-purpose water hose for a wide range of uses listed as:

- Municipal,
- Construction,
- Institutional,
- Landscape,
- Golf or
- Agricultural applications.



Value: Lightweight, yet durable and thick outer wall. Non-conductive hose, minimum electrical resistance, greater than one (1) megohm per inch of hose length at 1000 DC volts. Non. Very smooth finish good for golf greens and clear material provides visual confirmation when used with applicators.

Working Pressure: 150 Psi

Burst Pressure: 600 Psi

Tube: Clear flexible PVC, RMA Class B (medium oil resistance)





Reinforcement: Polyester Fiber

Temperature Range: -10°F to 158°F (-23°C to 70°C)

Hose Diameters: (Imperial and Metric values)

| | 3/4" | |
|-----|-------------------|--|
| ID: | 0.74 to 0.78" | |
| | (18.7 to 19.7 mm) | |
| OD: | 1.00 - 1.06" | |
| | (25.4 to 27.0 mm) | |

| 1" |
|-------------------|
| 0.98 to 1.02" |
| (25.0 to 25.8 mm) |
| 1.31 to 1.36" |
| (33.4 to 34.5 mm) |

Weight/ft. (imperial and metric values)

| 3/4" |
|----------------|
| 0.200 lbs. max |
| (0.09 kg) |

| 1" | |
|----------------|--|
| 0.340 lbs. max | |
| (0.15 kg) | |

Weights by Hose Lengths: (Imperial and Metric values)

| | Hose Length | | |
|------|---------------------|----------------------|----------------------|
| Size | 50' (15.24m) | 75' (22.86m) | 100' (30.48m) |
| 3/4" | 10.0 lbs. (4.54 kg) | 15 lbs. (6.80 kg) | 20.0 lbs. (9.07 kg) |
| 1" | 17.0 lbs. (7.71 kg) | 25.5 lbs. (11.57 kg) | 34.0 lbs. (15.42 kg) |

Available Lengths: 50', 75' & 100', (custom lengths upon request)

Ordering Information:

| ¾" Hose Diameters | | | | | |
|-------------------|----------------|-------------------------|--|--|--|
| Model No. | Length Ft. (m) | Description | | | |
| H75-050C | 50' (15.24m) | ¾" UltraMax™ Clear Hose | | | |
| H75-075C | 75' (22.86m) | ¾" UltraMax™ Clear Hose | | | |
| H75-100C | 100' (30.48m) | ¾" UltraMax™ Clear Hose | | | |
| 1" Hose Diameters | | | | | |
| H10-050C | 50' (15.24m) | 1" UltraMax™ ©lear Hose | | | |
| H10-075C | 75' (22.86m) | 1" UltraMax™ Clear Hose | | | |
| H10-100C | 100' (30.48m) | 1" UltraMax™ Clear Hose | | | |

Couplings: Machined brass, FHT or MHT

 $\frac{3}{4}$ ": Male and female garden hose fittings (3/4"- GHT threads) & 1.075" ID ferrules 1": Male and female garden hose fittings (1"- NPSH threads) & 1.380" ID ferrules

Origin of Manufacturer: United States

Branding / Identification on Layline of Hose:

"UltraMax Clear 3/4" (19.1mm) 150 PSI W.P. made in USA Underhill logo" date code "UltraMax Clear 1" (25.4 mm) 150 PSI W.P. made in USA Underhill logo" date code